

 1. Safety precautions

The products involved are all open-type housing designs. Therefore they should be installed in a control cabinet that is free of airborne dust, humidity, electric shock, and vibration. The cabinet should prevent non-maintenance staff from operating the products or accidents from happening in case danger and damage may occur on the products.

M
Please refer to the M series hardware manual for more detailed information.

2. General electrical and environmental specifications

2.1 General electrical specifications				
Model	W	Rated power W	Rated voltage	
HCMXB-2RS232-200-BD	0.15	0.15	DC5V DC4.75V~DC5.25V	DC5V, voltage range DC4.75V~DC5.25V
HCMXB-2RS485-200-BD	0.125	0.125		

*
*Note: All models are featured by the SELV input type.

2.2 Environmental requirements				
	Item		Specifications	
	Altitude	≤2000m	≤2000m	
	Operating environment		Installation within a control cabinet, open-type and indoor use	
	Operating temperature	0~50	0~50	
	Storage temperature	-25~75	-25~75	
	Ambient humidity	5~95%RH	5~95%RH (non-condensation)	
	Vibration resistance	5~150Hz X/Y/Z 1g/3.5mm	5~150Hz (X/Y/Z direction, 1g /3.5mm displacement)	
	Pollution degree		Level 2	
	Cooling method		Natural air cooling	
	IP rating	IP20	IP20	
	Enclosure material		Self-extinguishable	

*

Terminal	AWG (Wire width)	mm (Wire stripping length)	N Pressure	N Wire pulling force	 剥线长

--

--

--

--